

AC 7/11/22KW

Commercial Charger

GB/T



TYPE2



TYPE3



Features

- 7-22KW Single Output
- Dynamic Load Balancing
- Improve Your ROI
- OCPP 1.6J Compliance Backend System



Parameters

Specifications			
Model	B5		
Rated Power	7KW	11KW	22KW
Input/output Voltage	AC220V+15%	AC380V+15%	AC380V+15%
Net weight	5.3KG	5.4KG	5.4KG
Maximum Current	32A	16A	32A
Interface	4.3" color touch LCD	Wiring Method	Bottom incoming
Installation	Wall-mounted / Floor-standing	Gun Number	1
Cable Length	5M	Dimensions (W * H * D)	240*355*120mm
Environment			
Operation Temperature	-25°C-55°C	Operation Altitude	≤2000M
Operation Humidity	<95%, non-condensing	Protection Rate	IP55
Cooling Types	Natural Cooling	Overcurrent Protection Threshold	≥110%
Operating			
Charging Mode	Auto-Full	Payment Methods	QR Code/Swipe card
Charging Methods	Swipe card/APP Launch	Network Connection	Ethernet/WIFI/4G(optional) OCPP1.6J (Upgradable to 2.0)
Security			
Charging Standards	IEC61851-2017 IEC62196-2017 GB/T 18487.1-2023 GB/T 20234.1-2023		
Protection	Over current protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over temperature protection		