

# AC 7/11/22KW

## x 2 CONNECTORS Commercial Charger

GB/T



TYPE2



TYPE3



### Features

- Single output
- Dynamic Load Balancing
- Wall-mounted & floor-standing
- OCPP 1.6J Compliance Backend System



### Parameters

Specifications				
Model	EVC-AC-B6-14KW	EVC-AC-B6-22KW	EVC-AC-B6-44KW	
Rated Power	7KW*2	11KW*2	22KW*2	
Max Output Current	32A*2	16A*2	32A*2	
Interface	4.3" color touch LCD		Wiring Method	Bottom incoming
Installation	Wall-mounted / Floor-standing		Input Frequency	50±3Hz
Input/output Voltage	AC220V±15%			AC380V±15%
Cable Length				5M
Gun Number				2
Net weight				15.5KG
Dimensions (W * H * D)				366mm*550mm*153mm
Environment				
Operation Temperature	-25°C~55°C	Operation Altitude	≤2000M	
Operation Humidity	<95%, non-condensing	Protection Rate	IP55	
Cooling Types	Natural Cooling	Overcurrent Protection Threshold	≥110%	
Operating				
Charging Mode	Auto-Full	Payment Methods	QR Code/Swipe card	
Charging Methods	Swipe card/APP Launch	Network Connection	Ethernet/WIFI/4G(optional) OCPP1.6J (Upgradable to 2.0)	
Security				
Charging Standards	IEC61851-2017 IEC62196-2017 GB/T 18487.1-2023 GB/T 20234.1-2023			
Protection	Over current protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over temperature protection			

