

AC TWO POINT

Ebike Charging Station

Features

- No need internet
- OTP password to start
- Full-charge auto-off
- No-load Auto Stop
- Overload protection
- Power-off memory



Parameters

Specifications			
Model	M2		
Plug No	TWO POINT		
Voltage	AC220±15%		
Power	3500W each way		
Ac Frequency Range	50Hz±3%		
Installation	Wall-mounted		
Dimensions (W * H * D)	290*90*60mm		
Electrical			
Operation Temperature	-20°C~50°C	Operation Altitude	<2000M
Operation Humidity	5%~95%	Protection Rate	IP55
Cooling Types	Natural Cooling	Overcurrent Protection Threshold	≥110%
Operating			
Network Connection	Offline		
Charging Mode	Auto-Full		
Charging Methods	RFID card swiping		
Security			
Protection	Over current protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over temperature protection		

AC TEN POINT

Ebike Charging Station

Features

- Online control/Manage system/APP
- Multiple payment methods
- Ocpp1.6j can deploy on EVSE system



Parameters

Specifications			
Model	M10		
Plug No	TEN POINT		
Voltage	AC220±15%/AC120±15%		
Power	800W each way		
Ac Frequency Range	50/60 Hz±10%		
Installation	Wall-mounted		
Dimensions (W * H * D)	290*400*80mm		
Electrical			
Operation Temperature	-30°C~70°C	Operation Altitude	<2000M
Operation Humidity	<95%, non-condensing	Protection Rate	IP55
Cooling Types	Natural Cooling	Overcurrent Protection Threshold	≥110%
Operating			
Network Connection	4G / WIFI / LAN		
Charging Mode	Auto-Full		
Charging Methods	IC card / APP Bluetooth / Auto charging	Protocol	Ocpp1.6j
Security			
Protection	Overcharge protection, Power measurement, Automatic meter reading		