

DC 120-240KW

All-in-one Fast charger

GB/T



CCS2



CCS1



Features

- Easy To Maintain, Safe To Use
- Compact In Size
- Built With Safety Isolation
- GB/T/CCS2/CCS1



Parameters

Specifications				
Model	D6S			
Rated Power	120KW	160KW	180KW	240KW
Maximum Current	400A	532A	600A	798A
(each connect max to 250A)				
Interface	4.3" color touch LCD			
Advertising screen	33-inch HD			
Installation	Floor-stand			
AC Power Supply	AC380V+15%			
Measurement Accuracy	0.5			
Wiring Method	Bottom incoming			
Output Voltage	DC200-1000V			
Cable Length	5M			
Network Connection	Ethernet/4G(Protocols OCPP 1.6J) (Upgradable to 2.0)			
Electrical				
Overcurrent Protection Threshold	>250	Dimensions (W * H * D)	915*1695*555mm	
Voltage Stabilization Accuracy	±0.5%	Steady Flow Accuracy	±1%	
Ripple Factor	<1%	Efficiency	≥95%	
THD	≤5% (≥50%loading)	Power Factor	≥0.98	
Environment				
Operation Temperature	-30°C~+50°C		Operation Altitude	≤2000M
Operation Humidity	<95% non-condensing		Protection Rate	IP55
Security				
Charging Standards	IEC62196-2017	IEC61851-2017	SAEJ1772 GB/T 18487.1-2023	GB/T 27930-2023
Protection	Over current protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over temperature protection			

